

URS FOR BLOWER

GENERAL SPECIFICATIONS

TYPE

CAPACITY AT SUCTION (nm³/hr)

DISCHARGE PRESSURE (kg cm²g)

INLET PRESSURE (bar)

INLET TEMPERATURE (deg C)

QTY REQUIRED (nos)

MECHANICAL DESIGN

DRIVE

OPERATION

MOTOR TYPE

MOTOR POWER (kw)

RECOMMENDED MOTOR (hp)

MOTOR SPEED (rpm)

DISCHARGE TEMPERATURE (deg C)

VARIABLE FREQUENCY DRIVE

REQUIRED NOISE LEVEL WITHOUT ACCOUSTIC HOOD (dba)

REQUIRED NOISE LEVEL WITH ACCOUSTIC HOOD

MATERIAL OF CONSTRUCTION

CASING

LOBE

SIDE COVER

SHAFT

GEARS

BEARINGS

ACCESSORIES

COMMON BASE FRAME

SUCTION FILTER

SAFETY VALVE

V BELTS

V BELTS GUARD

NRV, PRESSURE GUAGES

ALL FIXING NUT BOLTS

DRIVE AND DRIVEN PULLEYS

INTERCONNECTING PIPING

SET OF FOUNDATION BOLTS

ANTI VIBRATION PADS

APPLICATION

Please specify

REMARKS

please write specification

